

```

const int analogInPin = A0;

int sensorValue = 0;

int KEY ;

int NEWKEY ;

int OLDKEY = 0;

int OK = 0 ;

int FLAG = 0;

int coun = 0;

int coun1 = 0;

int look = 0;

int chk[16] = {0,100,260,385,482,530,587,630,660,688,714,735,753,769,784,800}//
set array comparision value

//*****
*****
#include

long irKeyCodes[16] = {

    0x00000000, 0x40BFF807, 0x40BF7887, 0xC03FC03F,      // correspond
to Keypad button '1', '2', '3','4'

    0xC03F40BF,0x40BF00FF, 0x00000000, 0x00000000,      // correspond
to Keypad button '5', '6', '7','8'

    0x00000000, 0x00000000, 0x00000000, 0x00000000,      // correspond to Keypad
button '9', '10', '11','12'

    0x80FFC13E, 0x80FFE11E, 0x80FFD12E, 0x80FFF10E      // correspond
to Keypad button '13', '14', '15','16

};

IRsend irsend;

//*****
*****


void setup() {

```

```
Serial.begin(9600); //Set Baud Rate:  
}  
  
void loop() {  
  
    sensorValue = analogRead(analogInPin);  
    delay(15);  
  
    aaa:  
    if (FLAG == 0)  
    {  
        if (chk[0]<=sensorValue && sensorValue  
        {  
            KEY = 1 ;  
        }  
        else if (chk[1]<=sensorValue && sensorValue  
        {  
            KEY = 2 ;  
        }  
        else if (chk[2]<=sensorValue && sensorValue  
        {  
            KEY = 3 ;  
        }  
        else if (chk[3]<=sensorValue && sensorValue  
        {  
            KEY = 4 ;  
        }  
        else if (chk[4]<=sensorValue && sensorValue  
        {  
            KEY = 5 ;
```

```
}

else if (chk[5]<=sensorValue && sensorValue

{

KEY = 6 ;

}

else if (chk[6]<=sensorValue && sensorValue

{

KEY = 7 ;

}

else if (chk[7]<=sensorValue && sensorValue

{

KEY = 8 ;

}

else if (chk[8]<=sensorValue && sensorValue

{

KEY = 9 ;

}

else if (chk[9]<=sensorValue && sensorValue

{

KEY = 10 ;

}

else if (chk[10]<=sensorValue && sensorValue

{

KEY = 11 ;

}

else if (chk[11]<=sensorValue && sensorValue

{

KEY = 12 ;

}
```

```

else if (chk[12]<=sensorValue && sensorValue
{
    KEY = 13 ;
}

else if (chk[13]<=sensorValue && sensorValue
{
    KEY = 14 ;
}

else if (chk[14]<=sensorValue && sensorValue
{
    KEY = 15 ;
}

else if (chk[15])
{
    KEY = 16 ;
}

else if (sensorValue>1000 )           ///
{
    KEY = 0;
}
}

NEWKEY = KEY;                      //save value of KEY to NEWKEY
if ( NEWKEY == OLDKEY)      // if NEWKEY == OLDKEY then OK + 1
{
    OK++;
}

```

```
else
{
    OK = 0;           // if not, then  OK=0
}

OLDKEY = NEWKEY;

if(OK>=5)           // if OK =5  print the value

{
    Serial.print("KEY = ");
    Serial.println(NEWKEY);
    Serial.println(sensorValue);

    Serial.print("look = ");
    Serial.println(look);

    if (NEWKEY !=0)

    {
        switch(NEWKEY){


```

case 1:

```
    FLAG =1;
    break;
```

case 2:

```
    FLAG =1;
    break;
```

case 3:

```
    FLAG =1;
    break;
```

case 4:

```
    FLAG =1;
    break;
```

case 5:

```
FLAG =1;  
break;  
case 6:  
FLAG =1;  
break;  
case 7:  
FLAG =1;  
break;  
case 8:  
FLAG =1;  
break;  
case 9:  
FLAG =1;  
break;  
case 10:  
FLAG =1;  
break;  
case 11:  
FLAG =1;  
break;  
case 12:  
FLAG =1;  
break;  
case 13:  
FLAG =1;  
break;  
case 14:  
FLAG =1;  
break;
```

case 15:

FLAG =1;

break;

case 16:

FLAG =1;

break;

}

}

if(NEWKEY>0)

{

coun1++;

}

if(coun1>5)

{

coun1=0;

irsend.sendNEC(irKeyCodes[NEWKEY], 32);

look++;

}

if (sensorValue>950)

{

coun++;

}

if(coun>1)

{

FLAG =0;

```
coun = 0;  
    goto aaa;  
}  
}  
}
```

This article was published on Monday 09 January, 2012.